# Aurender Quick Start Guide





# Table of Contents

What Is Required	 3
STEP 1: Download the Aurender Conductor App	 4
STEP 2: Connect the Aurender to Power	 6
STEP 3: Connect the Aurender to Local Area Network	 6
STEP 4: Connect Conductor App to Aurender and Update Software	 8
STEP 5: Connect to DAC	 9
SSD/HDD Installation	 10
Preparing Internal Music Content	 12
Preparing Streaming Music Content	 15
Playing Music	 18
Remote Support	 19
Important Notice: Improper Shut Down Can Cause Damage	 20

## What Is Required

- 1. Aurender Music Server itself
- 2. A wired Ethernet connection to the Aurender
  - CAT6 or higher Ethernet cable is required for sustained performance
  - In case a direct Ethernet connection from your router is not feasible, you may use a wired connection from Wireless Access Point, WiFi Extender, or Ethernet-over-Powerline.
- 3. A mobile device to run the Aurender Conductor app
  - Apple iPad with iPadOS 13 or later. The latest iPad Air or iPad Pro are recommended for the best performance.
  - iPhone with iOS 13 or later
  - Android phone with Android 10.0 or later
  - Android tablet with Android 10.0 or later
- 4. WIFI router

Your mobile device running Aurender Conductor app must be connected wirelessly to the same network the Aurender is attached to communicate with each other. A gigabit–speed router is highly recommended for the best result and stable content streaming.

\* If any hardwired Ethernet connection is unavailable, you may use a USB WiFi adapter to create an isolated wireless network between the Aurender and a mobile device. In this scenario, there will be no Internet access for streaming content to your Aurender. Please consult support@aurender.com for compatible USB WiFi adapters.


## STEP 1: Download the Aurender Conductor App

### iPad

1. Open the App Store on your iPad



2. Search for the "Aurender Conductor" app. Tap the "GET" button to download and install.





#### iPhone

1. Open the App Store on your iPhone



2. Search for the "Aurender Conductor for iPhone" app. Tap the "GET" button to download and install.






### Android

1. Open Play store on your Android Phone



2. Search for the "Aurender Conductor" app. Tap the "INSTALL" button to download and install.



## ACS-10/ACS-100/A30 Users

1. Open the App Store on your iPad [

2. Download and install the "ACS Manager" or "A30 Manager" app for iPad in addition to Conductor. You will need this to configure and operate ACS-10/ACS-100/A30-only features like CD ripping, meta-data editing, and more.

Filters ✓ ACS Manager	Q Aurender acs manager	ACS Manger for iPad	ACS Manger for Android
Music Music Music Music Music Music Music Music	$\begin{array}{c} \hline \\ \hline $		
	$ \begin{tabular}{ c c c c c } \hline $ $ $ $ $ $ $ $ $ $ $ $ $ $ $ $ $ $ $	A30 Manager for iPad	A30 Manager for Android
Today	Games Stapps		

## STEP 2: Connect the Aurender to Power

Using the included power cable, connect your Aurender to a 110/220V (depending on your region) electrical outlet or a power conditioner/surge protector.

Note: Your Aurender product comes with a generic IEC power cable. However, many Aurender customers choose to use an upgraded power cable for optimal sound. Please consult your HIFI dealer for cable recommendations.


## STEP 3: Connect the Aurender to Local Area Network

#### Aurender Server

Your Aurender server must be connected to your router via a hard-wired Ethernet connection. Aurender servers do NOT have any WiFi connectivity (this is by design – most WiFi networks are unreliable and subject to drop-outs and limited bandwidth).

In cases where your listening room location makes it physically impossible to run an Ethernet connection back to the router, you may use a WiFi extender or Ethernet–over–powerline adapter to es-tablish connectivity. Please contact Aurender Support for assistance.

Below is a diagram of a common connection schematic. Your network configuration may vary:



#### USB WiFi Adapter (optional)

In case your listening room does not have access to a wired LAN connection, you can use a USB WiFi adapter ("dongle") to establish a one-to-one connection between your iPad and your Aurender. In this scenario, you will not have Internet access for streaming, but you will be able to browse and play content that is stored on your Aurender's local storage:

1. Consult support@aurender.com for an up-to-date list of compatible USB WiFi adapters.

- 2. Plug the USB WiFi adapter into a USB data port on the back of your Aurender.
- 3. In your iPad WiFi settings, select the WiFi network that is named after your Aurender.
- 4. The default password will be "aurender12345"

THE FOLLOWING SECTION APPLIES ONLY TO ACS10/ACS100 UNITS. IF YOU DO NOT HAVE EITHER OF THESE MODELS, MOVE ON TO SECTION 4:


#### ACS10 as Stand-Alone Server - LAN Connection

The ACS10 is equipped with isolated LAN ports for greater noise reduction. If using the ACS10 as a standalone music server, plug the Ethernet cable into the "LAN 1 2X Isolated" port:



#### ACS10 as Companion Unit - LAN Connection

If you are using ACS10 as a companion to another Aurender server/player, refer to the diagram below for optimal connection scheme which provides double isolation for the primary Aurender server/ player:




For best performance, do not stack ACS10 and other Aurender product directly on top of one another. Separate them to different shelves for proper vibration isolation. You can even place them in different rooms entirely if your home's Ethernet wiring allows.

In this ideal scenario (ACS10 + other Aurender server/player), the ACS10 acts as a filter to isolate your primary Aurender player from any noise transferred over Ethernet.

## STEP 4: Connect Conductor App to Aurender and Update Software

1. In the iPad Settings (), confirm that your iPad is connected to the correct WiFi network.

2. Open the Aurender Conductor app and go to Settings 🔯 > Aurender. Select your Aurender to connect:



3. Now that you are connected to your Aurender, confirm that your software is up to date by going to the "Software Update" section of the Conductor Settings Menu. If a software update is available, you will be prompted to download and then install the software update.

5:01 PM Wed Jul 24	A100	0-004d33 (IP:192.168.1.86)	🗢 48% 🔲
= 14 🕨	Settings	Software Update X	nposer
0:00	Aurender	Check Beta version	/24 ★ 🌣
	Disk Information	Check for latest beta version	···· 0
	Scanner		
	Front Display		ong
☆☆☆☆☆	General	Update Aurender System Software : 5.17.15	
	Software Update	Current version : 5.15.30	ong
▶ Queue	Aurender File Share		

Note: Conductor will temporarily lose connection to the Aurender as the unit reboots during the update process. Please quit the Conductor app and reopen it once the update has been completed.

## STEP 5: Connect to DAC

Before connecting your Aurender to a DAC, integrated amp, or preamp, please make sure that the device you are connecting to is powered OFF before you make the connection. This will ensure a solid "handshake" between the Aurender and DAC, and it will prevent accidental damage to your system by "hot-swapping" cables.

#### USB

All Aurender music servers feature dedicated USB audio outputs. These USB audio outputs are filtered and isolated for the purest possible transmission of the digital signal via USB. The dedicated USB audio port is clearly marked on the back of your Aurender (location varies by model). For best USB audio performance, please be sure to use the dedicated USB audio port (not to be confused with the USB data ports) for audio.

A note on USB Compatibility – As a general rule, if the DAC does NOT require drivers to work with an Apple computer, then it will work with Aurender's USB output. If you are uncertain, please check with your DAC manufacturer to confirm it is compatible with a Linux-based server.

#### SPDIF (includes AES/EBU, Coax RCA, BNC, Optical)

N20, W20SE, and N30SA models benefit from a suite of SPDIF outputs in addition to USB. The SPDIF output section is controlled by the extremely precise OCXO clock. Therefore, in many cases, your DAC may sound better when connected to one of these outputs. All digital outputs are active at all times. Which output sounds best will depend on your DAC.

To use these outputs, connect the corresponding cable from the desired output on the Aurender to the input of the same type on your DAC.

In addition to USB, the model N200 features a coaxial digital output. This is provided for DACs without a USB input or for those who prefer the sound of an SPDIF connection. The N200 uses a precise TCXO oscillator in the re-clocking domain of the XMOS processor.

For more information on advanced hookups especially regarding these specific models, please see the Web Manual at www.aurender.com/user-guides

#### Analog Outputs - (RCA/XLR)

A15, A20, and A30 have both RCA and XLR analog outputs (A200 has RCA analog outputs only).

Since the A200, A15, A20, and A30 have a high–quality digital volume control, you can run these analog outputs into your preamp, or straight into your power amplifier if you like. If connecting straight into your power amplifier, it is essential that you make sure the volume on your A200, A15, A20, or A30 is turned down before playing music. Failure to do so may cause damage to your system!

If you are using a preamp or integrated amp, we recommend setting the volume output to "direct" mode for best performance.

## User-Installable SSD/HDD Guide

THE FOLLOWING APPLIES ONLY TO AURENDER MODELS WITH USER-INSTALLABLE STORAGE SLOTS AS PICTURED BELOW. IF YOU DO NOT HAVE ONE OF THESE MODELS, OR IF YOU DO NOT INTEND TO INSTALL AN SSD/HDD FOR LOCAL MUSIC CONTENT STORAGE, PLEASE MOVE ON TO THE NEXT SECTION.


Caution Any data on an SSD/HDD that you install will be permanently erased during the formatting process.

Aurender recommends Samsung QVO or EVO series internal SSD drives, and Western Digital or Seagate HDDs.

Most 2.5" HDD or SSD is compatible with Aurender models featuring user-installable storage drives.\* However, there is a limitation in the physical form factor.

\*Note: ACS100 can accommodate any 2.5" HDD or SSD with a maximum height of 7 mm. Some of Seagate's higher capacity (3–5TneyB) 2.5 " Barracuda drives are NOT compatible with ACS100 due to their height.

1. Unscrew and eject the disc enclosure tray[s] before turning the unit on.



2. Install SSD[s]/HDD[s] into the tray[s] as pictured.



3. Gently push the tray[s] containing SSD[s]/HDD[s] into the slot. After tray is in position, turn screws clockwise to secure tray.

4. Turn the power on and connect to the Conductor app.


5. If the newly installed disk needs to be formatted, a "Format" button will appear under the Disk information. Press the "Format" button to proceed.

6. Follow the prompt to confirm that you want to delete all content and format the drive for use.

7. The Conductor app will display a popup message indicating that the SSD/HDD formatting has begun. The Aurender will restart after formatting is complete.




8. After formatting is complete and the Aurender has rebooted, confirm that the newly installed and formatted drive[s] are recognized by checking "Disk Information" menu.



## Preparing Internal Music Content

#### **USB Smart Copy**

- 1. Connect a USB hard drive to one of the USB data ports on the back of your Aurender.
- 2. Select the "Folder" tab from the top row of buttons. And then select "USB"




3. Select the folder[s] from the USB drive you wish to copy to Aurender and then tap "Copy to"

	Song Artist Album Genre	Composer Conductor Folder Test Misc.	Q 30 DSD 16/24	<b>∂</b> ≮oum	ل <b>آ</b> Genre C	Composer C	Sonductor	Folder
	< Root	USB	Copy status Copy to		USB		٦	j 🖸
	🧭 My Music							
ፚፚፚፚ	System Volume Informati	on			My Music	٦		>
					NDZI			
Queue Playlist Editor					NPKI			
					System Volu	ume Informatio	on	
					Untitled_201	180320_07044	6.PDF	
4. Select the target f	older on your Aurer	nder			Untitled_201	180320_07051	5.PDF	
	Song Artist Album Genre	Composer Conductor Folder	Q 30 DSD 16/24 🌟 🛱		lect a targ	et folder		
	< Root	USB	Copy status Copy to				+ Ne	ew Folder
	Select a ta	arget folder	0					
$\bigcirc$	Music1				Music1	7		
****					Music2			
▶ Queue 🎤 Playlist Ed								
Queue 🛞								
Consume mode off								
	Cancel	Select						
						START COP	/	


#### NAS Smart Copy

If your music is stored on a NAS, you can use Smart Copy to copy contents from the NAS to the Aurender internal storage.

1. Sign into your NAS by going to the NAS Server section of the Conductor Settings Menu. Tap "Browse NAS Server" to find your NAS.



2. Select your NAS from the list of found servers, then enter the Username and Password to connect.



3. Follow the "USB Smart Copy" steps, except select "NAS" instead of "USB" in step 2.

#### ACS Companion Mode

If you are using an ACS as a companion or in addition to another primary Aurender server, you will want to "merge" the library contents so that your primary Aurender's music library is based on content stored on the ACS plus its own local storage.

- 1. Go to the "ACS" section of the Conductor Settings Menu
- 2. Tap "Select ACS to connect"
- 3. Follow the on-screen prompts to connect to your ACS and merge your library.

<i>□</i>  •		Settings			ACS		×		
0:00		Aurender		Aurender	Content	Server		/24 ★	\$
		Disk Information	Configure	ed ACS				Copy to	0
		Scanner	oonngare		Not set				
		Front Display	_						
☆ ☆ ੯	3 12 12	General		Select an	ACS to co	nnect			
		Software Update	Use this op applicable.	tion to connect v	vith an ACS	on your netw	vork, if		
▶ Que Queue	ue	Aurender File Share							
	node of	NAS Server							
		Advanced							
		Advanced 2							
		Streaming							
		ACS							
	16:38	3 <b>-1</b> l 후 🗖	) <sup>,</sup>	16:39			ad *		
		Settings		<		ACS			
Ę	Sca	anner	>						
Ţ	Fro	nt Display	>	Linked A	CS			None	
₿	NA	S Server	>	With Exte Aurender v		age Mode			
(1)	Str	eaming	>	content as saved to e	a library.	Streaming			
00	Adv	vanced	>	With Centr Aurender V					
00	Adv	vanced 2	>	Streaming ACS. Internal ste				from	
00	TD	100	>					_	
ቀ	Aur	render File Share	>		Select	an ACS to	o link		
ይ	Clo	ne Aurender	>	Use this o network, if			ACS on y	our	
	AC	S	>						
A	MQ	A Core-Decoder Upgrade	>						
4	Bad	ckup & Restore	>						
¢	Sof	ftware Update	>						
							~		
	<b>F</b> brary	= <b>∫</b> Q (③) ⊂ Queue Search Settings Volu		Library	≡ <b>∫"</b> Queue	Q Search	کی Settings	<b>⊲))</b> Volume	

\* ACS10 is configured as RAID 1 (Mirror) when released from the factory. If you want to maximize the HDD capacity, please go to Settings>Disk Information in the ACS Manager app and click DELETE RAID. All contents will be deleted and you will see two HDDs after automatic formatting.

Please refer to the Web Manual at www.aurender.com/user-guides for more information.

## Preparing Streaming Music Content

To sync your Aurender with your streaming service subscriptions, simply log in via the Conductor app:

- 1. Go to the "Streaming" section of the Conductor Settings Menu
- 2. Select the available streaming service[s] to which you subscribe
- 3. Enter your username & password to connect

Song Artist Albur Settings		Conductor Foldo	X
lurender	<b>`</b>		
Disk Information	*** T	IDA	
Scanner	Accoun	t Information	
Front Display			
General	Email		
Software Update	Quality	ormal High	HIFI
Aurender File Share	Please subs	cribe to use TID	DAL
NAS Server			
Advanced	Logout	) (	og in
Advanced 2		oin TIDAL	
TD100 (USB Trigger)	More information at h		
Streaming	Login information stor device, you must rem information.		
ACS	internation.		
MQA Core-Decoder Upgrade			

Settings	✓ Qobuz ×	← Streaming	Streaming
Aurender		ତ୍ତ୍ର qobuz	
Disk Information			ତ୍ତ୍ qobuz
Scanner	Account Information	Username	ID
Front Display	Email	Password 🔌	Training and
General	Password	LOG IN	Password
Software Update	MP3 - 320kbps CD - 16bits / HiRes - 24bits / HiRes - 24bits / 44,1kHz up to 96kHz up to 192kHz	Quality	
Aurender File Share		MP3 - 320kbps CD - 16bits / 44.1kHz	Log in
NAS Server	Try 1 month free streaming (worth = 19,99€/£)	HiRes - 24bits / up to 96kHz	MP3 - CD - 16bits / HiRes - HiRes - 320kbos 44.1kHz 24bits / up to
Advanced	Logout Log in	HiRes - 24bits / up to 192kHz	320kbps 44.1kHz to 96kHz 192kHz
Advanced 2	Join Qobuz		
Streaming	HiRes streaming content is limited to the quality	Unknown	96K-I Want toYour Hand.wav 😽 🕨
ACS	level the suscriber chooses. If you set the quality level to HiRes, but have not subscribed to that	Unknown	Library Quoue Search Settings


\*If you subscribe to the highest quality streaming tier from your preferred streaming service, be sure to select the maximum quality possible when signing in. The free Tidal account is not supported by Aurender. Apple Airplay: Your Aurender server is also capable of receiving Airplay streams from your Apple devices. This feature is turned off by default but can be enabled in:


Conductor settings/Streaming/Stream to Aurender/Enable Service

Settings	<	Streaming to Au	ırender	×
Aurender				
Disk Information				
Scanner	9	Stream to A	urende	r
Front Display				
General				
Software Update	Er	hable service	$\bigcirc$	
Aurender File Share		Source : Not cor	nnected	
NAS Server				
Advanced		this is enabled, you der from AirPlay sup		
Advanced 2	, la on	aor nonn an ag sap	porting dorit	
TD100 (USB Trigger)				
Streaming				
ACS				
MQA Core-Decoder Upgrade				
Backup & Restore				
Clone Aurender				

Spotify Connect: Like the Airplay feature, this is off by default but is enabled in: Conductor Settings/Streaming/Spotify/Enable Service

Settings	Spotify	×
Aurender		
Disk Information		
Scanner		
Front Display		
General		
Software Update	Enable service	$\bigcirc$
Aurender File Share	Source : Not connected	
NAS Server	Open Spotify app	
Advanced	Ready to play some music?	
Advanced 2	Listen on your speakers or TV, using the Sp app as a remote.	potify
TD100 (USB Trigger)	Learn More	
Streaming		
ACS		
MQA Core-Decoder Upgrade		
Backup & Restore		
Clone Aurender		






## **Playing Music**

Now that you have loaded your personal music collection to the Aurender and synced up with your streaming services, you're ready to browse and play some music!


Aurender's playback engine operates on a "play queue" basis. When you select a song or group of songs to play, those files get cached to the internal solid state drive for best audio performance.

To add a song to the queue, simply tap on its name. It will be added to the queue according to the "Track Selection Default Behavior" settings which you can set under "General" in the Conductor App Settings Menu.

To add and play a complete album, you can press & hold on the album thumbnail and then select the desired playback behavior:



The songs will be added to the queue where you can tap on a song to play immediately, or let the album/playlist continue according to its order:




## Remote Support

#### The Aurender Commitment to Customer Support

Aurender's mission is to deliver the best user experience to our customers. That goes well beyond just building the best sounding and most reliable music servers.

We understand that Aurender products must be interfaced with other components and home networks where issues might arise. Anticipating and preparing for such situations is at the core of our customer service ethos. If support beyond this Quick Start Guide and additional documentation in the Web Manual is required, your first option is to go to the "Help" section of the Conductor Settings Menu. Then tap "Send Remote Support Email" to reach our technical support team:

Settings	Help X
Disk Information	Aurender User Guide
Scanner	Open user guide with Safari
Front Display	
General	Remote Support Request
Software Update	Send remote support email
Aurender File Share	
NAS Server	If you are encountering an issue or have questions about your Aurender, use this option to reach Technical Support. This will open an email window for requesting support. Please describe
Advanced	the problem in the space provided and press Send. Pressing "Send" will allow remote access to the Aurender unit, so that
Advanced 2	our engineers may diagnose and fix any software issues. Remote access will be disabled once the unit is inspected and/or repaired.
Streaming	Please keep the Aurender on and connected to the Internet
ACS	until we can contact you by email. Thank you for your patience and cooperation.
MQA Core-Decoder Upgrade	
Backup & Restore	
Clone Aurender	Reset Aurender Conductor settings
Help	Reset settings of the app
Software Version	This will not affect your contents, playlists or favourites. Only



In the email pop-up window, type in a brief description of the issue you are experiencing and click send.


Our technical support team will be able to analyze the activity logs of your Aurender to diagnose any problems. If necessary, our technicians can access your machine remotely and take corrective action to the software or firmware. This process is normally accomplished within 24–48 hours of the initiation of the request for Remote Support. Additionally, we provide customer technical support via telephone (for North America Only) at 888–367–0840. The hours of operation are Monday–Friday, 9am–6pm MST.

## Important Notice: Improper Shut Down Can Cause Damage

As with any computer, please avoid cutting power to the Aurender before properly shutting it down. Your Aurender needs to be shut down properly to avoid damage. (UPS-backed models will shut down properly, even when you abruptly removed power from the Aurender, but the proper shutdown is always recommend-ed.)

There are 2 ways to shutdown or restart your Aurender:

1. Press and hold the "play" button in the Aurender Conductor app (iPad only). From the pop-up, you can choose "Restart" or "Turn off."



Settings	Aure	ender X	16:00
			Aurender Ba
Aurender	Language		Date & Time
Disk Information	Aurender Name	A30Eric	Metadata Language
Scanner			
Front Display	IP Address	192.168.1.203	Network
General	Subnet Mask	255.255.252.0	Aurender Name
Software Update	Gateway	192.168.1.1	IP Address
Aurender File Share	Galeway	192.100.1.1	Subnet Mask
	DNS	127.0.0.1, 8.8.8.8	Gateway
NAS Server	MAC Address	00:23:f2:00:57:00	DNS
Advanced			MAC Address
Advanced 2			
TD100 (USB Trigger)	Power Control	1	Power Control
Streaming	Pes	start	Re
ACS			Shut
MQA Core-Decoder Upgrade	Turi	n off	Ē <b>≣</b> Library Queue S

>

55.252.0

2. Press and release the power button on the face of the Aurender itself. It will start to flash and on the screen, it will say "shutting down...Please wait." Note: in some cases, you may have to push the power button twice: once to "wake it up" and then again to shut it down.

## PLEASE DO NOT PRESS AND HOLD THE POWER BUTTON AS THIS CAUSES A FORCED SHUT DOWN.

During the Aurender shut down sequence, the power button backlight will pulse, and the screen will read "Shutting Down...Please Wait."

Only after the screen has gone black and the power light is dim, it is safe to flip the power switch on the back.

Failure to shut the Aurender down properly when turning it off or rebooting can cause severe damage to the unit's hardware.



Note: This document is intended as a provisional guide to getting started with your Aurender. In-depth instructions and explanations of the continual evolving features and functionality of Aurender software can be found in comprehensive Web Manuals at: **www.aurender.com/user-guides** 



Customer Service : support@aurender.com www.aurender.com Aurender America Inc. 20381 Lake Forest Drive, STE B-3 , Lake Forest, California 92630, USA www.aurender.co.kr (Korea) Aurender Inc. #1612, Obiz Tower, 126, Beolmal-ro, Dongan-gu, Anyang-si Gyeonggi-do, South Korea / ZIP 14057 iPad is the trademark of Apple Inc. Windows is a trademark of Microsoft Inc. All registered trademarks belong to their respective owners.

# D aurender

www.aurender.com