

# The Art of Music Reproduction



## 3510 Stereo Amplifier

### Outputs

Power Output (Stereo) :	110W per channel at 1kHz into 8 Ohms
Frequency Response :	20Hz - 20kHz $\pm$ 0.5dB
Total Harmonic Distortion :	<0.015% at rated output, ref. 1kHz
Signal to Noise Ratio :	>100dB, ref. rated output
Channel Separation :	>60dB, 20Hz - 20kHz

### Inputs

Input Impedance :	18K Ohms
Input Sensitivity :	1.85V @ 1kHz

### General

Mains Supply :	110/120V or 220/240V, 50/60Hz (factory set)
Fuse :	T8AL for 110/120V units T4AL for 220/240V units
Power Consumption :	<400W, 8 Ohms load both channels driven
Dimensions (HxWxD) :	115mm x 440mm x 300mm
Net Weight :	12kg
Gross Weight :	14kg

### Features

- 110W RMS per channel into 8 Ohms
- Ideal for driving difficult speaker loads in bi-amping mode with 3510 Integrated Amplifier
- High capacity custom-made toroidal power transformer and power supply capacitors
- High quality capacitors used in the signal path
- Clean and extended low frequency performance
- Full aluminium casework and extruded front panel to control resonance and stray electromagnetic fields
- Three year guarantee
- Available in black or titanium

