



PowerQuest **303** **505** **707**

Power Conditioners with Noise-Dissipation and Non-Sacrificial Surge Protection


audioquest




A direction-controlled cable is crucial to maximizing RF-Noise dissipation — Included with every PQ model.



2RU rack mount "ears" included in the box.



Better than the wall! Transient Power Correction and 45 amp on-demand current reservoir (shown) enable AQ Niagara level dynamics and jump-factor, like "the artist intended."



PQ-303 / PQ-505



PQ-707

	PQ 303	PQ 505	PQ 707
Power Cable with Flat-to-Wall Plug	PQ-416: 2m RF-Noise Dissipating cable with Semi-Solid Concentric Conductors using Long-Grain Copper (10amps @240V)	PQ-716: ZERO-Tech for uncompressed current transients and RF/ND-Tech for unprecedented Noise-Dissipation in this 2m RF-Noise Dissipating cable with Semi-Solid Concentric Conductors using Long-Grain Copper (10amps @240V)	
Linear Filtering More than -22dB	Linear Noise-Dissipation Differential Filter: 30kHz-1GHz	Ultra-Linear Noise-Dissipation Differential Filter: 30kHz-1GHz (PQ-505); 8kHz-1GHz (PQ-707) Common-Mode Filter: 30kHz-100MHz (both models)	
Non-Sacrificial Surge Protection	Withstands multiple AC surges and spikes up to 6000V/3000A without sustaining damage. Extreme-Voltage Automatic Shutdown at 270VAC.		
Transient Power Correction with Current Reservoir	N/A		Optimized electrical parameters and 45 amp Current Reservoir (25mS)
7 Outlets	4 x Linear-Filtered for Source / Constant-Current components (TVs, media streaming devices, etc.) 3 x High-Current for Variable-Current components (amplifiers, powered speakers & subwoofers)		
Rack-Mountable	Yes (2RU rack ears included)		
Dimensions and Weight	43cm W x 34cm D x 8.6cm H (9cm w/ feet attached); 4.65 kg	43cm W x 34cm D x 8.6cm H (9cm w/ feet attached); 4.9 kg	43cm W x 38cm D x 8.6cm H (9.4cm w/ feet attached); 7.6 kg
Euro Retail	€599,00	€799,00	€1.299,00