



# TORUS POWER

Engineered to perform & protect like no other

## Toroidal Isolation Power Conditioners

TORUSPOWER.COM

# TOT SERIES



Torus Power **TOT Mini** and **TOT Max** are ultra compact toroidal isolation power conditioners, and the most affordable products in the Torus line-up. The compact footprint and sloped face of TOT models make them convenient for use in almost any situation. They look sharp on a component shelf, or can be located elsewhere when space is at a premium.

The **TOT Mini** is rated at 7A (North American version), and 3A (International). It is the ideal accessory to provide true toroidal power conditioning for small or mid-power AV systems, or dedicated to video components (ie. flat panel TVs, projectors); or audio components (i.e. media sources, powered speakers, source components, etc.).

The **TOT Max** is rated at 15A (North American version) and 8A (International), and can be used in systems up to the rated output current.

**TOT** models provide a convenience USB-type charger as a bonus feature. **TOT** models provide basic circuit protection: series mode surge protection is available as a factory-installed option.

Both **TOT Mini** and **TOT Max** are designed to fit between 14" studs for in-wall applications. An optional in-wall mounting kit will be available in the near future.

### SPECIFICATIONS

	NORTH AMERICAN 120V		INTERNATIONAL 220V - 240V	
MODEL	TOT MINI	TOT MAX	TOT MINI CE	TOT MAX CE
CONFIGURATION	SAU (Stand-Alone Unit), RK (Rack Mount), IW (In-Wall Mount)			
CHASSIS HEIGHT	2U			
INPUT VOLTAGE	120V		220V - 240V	
OUTPUT VOLTAGE	120V		220V - 240V	
INPUT PROTECTION	1 X 7A FUSE	1 X 15A FUSE	1 X 3A FUSE	1 X 8A FUSE
OUTPUT CURRENT RATING	7A	15A	3A	8A
POWER RATING	819VA	1755VA	696VA	1840VA
FREQUENCY	60Hz		50/60Hz	
NUMBER OF OUTLETS	6	8	3	4
INLET TYPE	IEC 15A (UL) (SAU and RK)		IEC 10A (EC) (SAU and RK)	
OUTLET TYPE	NORTH AMERICAN 5-15R		SCHUKO CEE 7/7	
OUTPUT USB	5.1VDC nominal / 2300mA maximum			
WEIGHT (SAU)	25.1 lbs (11.4kg)	38.9 lbs (17.7kg)	25.5 lbs (11.6kg)	38.9 lbs (17.7kg)
WEIGHT (RACK)	26.0 lbs (11.8kg)	39.8 lbs (18.1kg)	26.4 lbs (12.0kg)	39.8 lbs (18.1kg)
WEIGHT (IN-WALL)	29.5 lbs (13.4kg)	43.3 lbs (19.7kg)	30.0 lbs (13.6kg)	43.3 lbs (19.7kg)
DIMENSIONS (SAU) WxHxD	318x101x268 (12.5x4.0x10.5)	318x101x369 (12.5x4.0x14.5)	318x101x268 (12.5x4.0x10.5)	318x101x369 (12.5x4.0x14.5)
DIMENSIONS (RACK)	480x88x271 (18.9x3.4x10.7)	480x88x373 (18.9x3.4x14.7)	480x88x271 (18.9x3.4x10.7)	480x88x373 (18.9x3.4x14.7)
DIMENSIONS (IN-WALL)	419x90x381 (16.5x3.6x15.0)	419x90x483 (16.5x3.6x19.0)	419x90x381 (16.5x3.5x15.0)	419x90x483 (16.5x3.5x19.0)



TOT MINI CE back



TOT MAX back

### Model Legend

#### TOT MINI CE RK

- Series
- Size
- Outlet Receptacle  
none = North American 5-15R
- \* Cabinet Configuration:  
none = Stand-Alone Unit    RK = Rack Mount 19"  
IW = In-Wall Mount

\* Add Cabinet Configuration code to RK or IW models at time of order.

### OPTIONS AVAILABLE:

- Series Mode Surge Suppression (factory installed)
- 19" Rack Faceplate/Adapter Kit
- In-Wall Adapter Kit

## Torus Power

Pitron Manufacturing Inc.  
 8 - 601 Magnetic Drive    T: 416-667-9914  
 Toronto, Ontario, Canada    F: 416-667-8928  
 M3J 3J2    tech@toruspower.com