

F 6X

6 CHANNEL MIXING CONSOLE WITH MULTI-FX

DESCRIPTION

RCF's next generation F Series mixers builds on the rich analog legacy found in the professional E Series, featuring high quality sound in four formats from 6 to 16 channels. A powerful tool for the musician and the sound enthusiast, entirely conceived and designed by the RCF R&D team. Housed in a sturdy metal chassis, each mixer features a full balanced audio path from input to output and the unique PRO DSP FX: 16 professional effects such as Reverbs (Halls, Rooms, Plates, Spring), Delays (Mono, Stereo and Multitap), Chorus, Flangers and Echoes. The models F-10XR, F-12XR, and F-16XR, include an USB audio interface, for stereo recording on computer-based DAW and 2-channel playback.



FEATURES

- 2 Mic/Line inputs
- 2 stereo line inputs
- One Aux/FX (post)
- Balanced main output audio path from input to output
- 16 presets PRO DSP internal FX
- Sturdy metal chassis
- External universal power supply
- Designed and engineered in Italy

TECHNICAL SPECIFICATIONS

Electronic specifications	Frequency Response:	20 Hz ÷ 20 kHz
	THD+N, 20dB gain, 0dBu out	<0,02

Inputs	Mic:	2
	Gain Range:	0 dB ÷ -50 dB
	Mic Inputs Impedance:	14 kohm
	Low Cut:	80 Hz
	Phantom Power +48V:	Yes
	Mono Line:	2
	Gain Selection:	20 dB ÷ -30 dB
	Line Input Impedance:	21 kohm
	Stereo Line:	2
	Gain Selection:	20 dB ÷ -30 dB
Stereo Line Input Impedance (kOhm)	15 kohm	

Outputs	Main MIX:	1
	FX Send:	1
	AUX Output:	1
	Phones:	1

Outputs specifications	Main Out Level:	28 dBu
	Aux Out Level:	28 dBu
	Phones Out impedance (ohm):	150 ohm

EQ	Input Channels EQ:	2 Shelving / 1 Generic
	Description:	High: +/-15 dB @ 10 kHz Shelving, Mid: +/-15 dB @ 1,250 kHz, Bell Low: +/-15 dB @ 100 Hz Shelving.

Auxiliary sends	FX POST:	1
------------------------	----------	---

Internal Effects	Send Effects:	1
-------------------------	---------------	---

Other features	Footswitch:	Yes
-----------------------	-------------	-----



Electrical specifications	Power supply:	External
	Voltage requirements:	100 V - 240 V
	Power consumption (MAX):	12 W
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Metal
	Color:	Black
Size	Height:	79 mm / 3.11 inches
	Width:	210 mm / 8.27 inches
	Depth:	255 mm / 10.04 inches
	Weight:	1.8 kg / 3.97 lbs
Shipping informations	Package Height:	122 mm / 4.8 inches
	Package Width:	378 mm / 14.88 inches
	Package Depth:	260 mm / 10.24 inches
	Package Weight:	2.75 kg / 6.06 lbs

PART NUMBER

- **17140088**

F 6X

EAN 8024530016135

